

**CHOATE
HALL &
STEWART**

**RECEIVED
CENTRAL FAX CENTER**

MAR 25 2004

OFFICIAL

A PARTNERSHIP INCLUDING PROFESSIONAL CORPORATIONS

Fax Transmittal Sheet

RECIPIENT	COMPANY	FAX	PHONE
Examiner Dougherty	Art Unit 2834	703 872 9306	

FROM	NUMBER OF PAGES 2
DATE March 25, 2004	CLIENT NUMBER 2001841-0011
PHONE	OPERATOR TIME SENT

COMMENTS Please deliver to Examiner Dougherty immediately. Thank you.

RETURN BY Inter-office Mail Hold for pick-up

This transmittal is intended only for the use of the individual or entity to which it is addressed, and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this transmittal is not the intended recipient, or the employee or agent responsible for delivering the transmittal to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately.

Proposed amendments to 10/041,919

1.-16. (Cancelled)

17. (Currently amended) An electromechanical device, comprising a substantially planar ~~electroactive~~ ceramic electroactive member having grooves defined on a planar surface of the member, whereby the grooves allow the member to bend to conform to a curved surface.

18. (Original) The electromechanical device of claim 17, wherein the device is an electromechanical sensor or actuator.

19. (Original) The electromechanical device of claim 17, wherein the device can conform to a curved surface having a radius of curvature no greater than 0.25".

20. (Original) The electromechanical device of claim 17, wherein the grooves are substantially parallel and the member can conform to a cylindrical surface.

21. (Original) The electromechanical device of claim 17, wherein the grooves are substantially concentric and the member can conform to a spherical surface.

22. (Original) An electromechanical device, comprising

a substantially planar bimorph electroactive ceramic member having slots defined in the member, whereby the slots multiply an electromechanical bending response of the bimorph member.

23. (Original) The electromechanical device of claim 22, wherein the device is an electromechanical sensor or actuator.

24. (Original) The electromechanical device of claim 22, wherein the slots are substantially concentric.

25. (Original) The electromechanical device of claim 22, wherein the slots are substantially parallel.